

**G41-3ISA ver 1.0**

|                               |  |
|-------------------------------|--|
| <b>Processor</b>              | Socket LGA775 for Intel Core2,Core 2 Quad,Core 2 Duo CPU |
|                               | FSB 533/800/1066/1333 CPU                                |
| <b>Chipset</b>                | Intel G41+ 82801GB                                       |
| <b>Memory</b>                 | 2* DDR3 DIMM,support 1333/1066/800MHz ,MAX. 8GB          |
| <b>Ethernet</b>               | Realtek RTL8111E Gbe Ethernet controllers                |
| <b>VGA</b>                    | Onboard Intel GMA4500 display card                       |
| <b>Expansion</b>              | 4*PCI slot   |
|                               | 1*PCIe 16x   |
|                               | 3*ISA  |
| <b>Audio</b>                  | Realtek ALC662 AC'97 Codec Audio                         |
| <b>Storage</b>                | 4*SATA   |
|                               | 1*Msata ,support SSD                                     |
|                               | 1*IDE  |
|                               | 1*CF   |
| <b>Back I/O Interface</b>     | 1*Keyboard interface                                     |
|                               | 1*Mouse interface  |
|                               | 4*USB  |
|                               | 1* COM   |
|                               | 1*VGA Port   |
|                               | 1* PRN Interface   |
|                               | 1*Audio interface(MIC, line out, line in)                |
|                               | 2* RJ45 LAN port   |
| <b>Internal I/O interface</b> | 1* Fpanel  |
|                               | 5* COM port  |
|                               | 1*Front Audio  |
|                               | 1* GPIO ,1*IrDA  |
|                               | 1*CPUFAN 4 PIN interface and 2*SYSFAN 3 PIN interface    |
|                               | 1*TPM Interface  |
|                               | 3*USB  |
|                               | 1* 24PIN + 4 PIN Power interface                         |
| <b>Accessories</b>            | 1 x CD driver  |
|                               | 1 x SATA cable   |
|                               | 1 x I/O shield   |
| <b>BIOS</b>                   | Award BIOS with 4Mbit Flash ROM                          |
| <b>Power Type</b>             | ATX Input  |
| <b>Operation Temp</b>         | -10 C-60 C   |
| <b>Operation Humidity</b>     | 10%~90% relative humidity, non-condensing                |
| <b>Size</b>                   | 305 x 244 mm,ATX   |

